



Product Specifications

Construction	Patterned Cut and Loop
Backing	Nexus® Modular
Dye Method	Beck Dyed
Nylon Fiber Type	Type 6,6 Nylon
Face Weight	37 oz./sy (1255 grams/m2)
Pile Density	8061 oz./y3 (298.91 kg/m3)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Stitches Per Inch	10 stitches/in (3.94 stitches/cm)
Standard Size	24" x 24" approx. (60.96cm x 60.96cm)
Standard Adhesive	Commercialon Premium Modular Adhesive
Standard Warranties	Nexus Modular Commercialon Adhesive for Modular Carpet & LVT
Optional Warranties	Tile Tabs

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Indoor Air Quality	GLP9670
Total Recycled Content	33.35%
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Installation Methods: Brick, Monolithic, Ashlar

Colorways



2255 Warm Toned



2258 Diffuse



2261 Haze Grey




2262 Neutral Density



2265 Grayscale



3106 Noise



3108 Shutter



3109 Sync



3110 Burst