



Product Specifications

Construction	Textile Composite
Backing	Polyester Felt Cushion
Dye Method	Solution Dyed
Wear Layer	Polyester - Applied Pattern
Pattern Repeat	N/A
Total Weight	4.5 oz - 5.2 oz/ square foot
Total Thickness	.205 inches
Dimensions:	12" x 48" modules
Standard Adhesive	Kinetex Adhesive
Optional Adhesive	Kinetex PreFix
Packaging	18 modules per box (72 sq.ft)
Standard Warranties	Kinetex Kinetex Adhesive
Optional Warranties	PreFix

Special Technologies

Kinetex ProTex®	Standard
------------------------	----------

Environmental Specifications & Tests

Recyclability:	100% Closed-loop Recyclable
NSF 140:	Platinum Certified
Indoor Air Quality	GLP2690
Total Recycled Content:	45%
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Installation Methods: Parquet, Herringbone, Basketweave, Ashlar

Colorways



2851 Database



2852 Firewall



2853 Cyber



2854 Modem




2855 Encryption



2856 Router



2857 Server



2858 Protocol



2907 System



2908 Wiring



2909 Tracks



2910 Maze



2911 Crisscross



2912 Complex



2913 Web



2914 Forum



2915 Directory



2916 Fiber



2917 Fabric



2918 Index