



Installation Methods: Brick, Monolithic, Ashlar, Quarter Turn

Product Specifications

Construction	Patterned Loop
Backing	Nexus® Modular
Dye Method	Solution/Yarn Dyed
Nylon Fiber Type	Encore® BCF (with recycled content)
Face Weight	21 oz./sq (712 grams/m ²)
Pile Density	7409 oz./y ³ (274.73 kg/m ³)
Pattern Repeat	N/A
Gauge	1/12 (4.72 rows/cm)
Stitches Per Inch	9.16 stitches/in (3.61 stitches/cm)
Standard Size	24" x 24" approx. (60.96cm x 60.96cm)
Standard Adhesive	Commercialon Premium Modular Adhesive
Optional Adhesive	TileTabs
Standard Warranties	Encore BCF (with ColorLoc Plus) Nexus Modular Commercialon Adhesive for Modular Carpet & LVT

Optional Warranties [Tile Tabs](#)

Special Technologies

Colorloc® Plus	Standard
ProSept® Antimicrobial	Optional
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Indoor Air Quality	GLP9716
Total Recycled Content	46.25%
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways



2007 Salt Creek



2008 Golden Canyon



2009 Jubilee Pass



2010 Furnace Creek



2011 Panamint



2012 Scottie



2013 Stove Pipe



2014 Badwater



2015 Dante's View



2016 Darwin Wells



2017 Mesquite Flat



2018 Black Mountain



2019 Zabriskie