Installation Methods: Parquet, Herringbone, Basketweave, Ashlar

Product Specifications

Construction	Textured Loop
Backing	Nexus® Modular
Dye Method	Solution Dyed
Nylon Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	25 oz./sy (848 grams/m2)
Pile Density	14178 oz./y3 (525.73 kg/m3)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Stitches Per Inch	10 stitches/in (3.94 stitches/cm)
Standard Size	12" x 48" approx. (30.48cm x 30.48cm)
Standard Adhesive	Commercialon Premium Modular Adhesive
Optional Adhesive	TileTabs
Standard Warranties	Encore SD Ultima Fiber Nexus Modular Commercialon Adhesive for Modular Carpet & LVT
Optional Warranties	Tile Tabs

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Indoor Air Quality	GLP9716
Total Recycled Content	45.85%
Flooring Radiant Panel	Class 1
Smoke Density	Less then 450 flaming (ASTM E 662)
Static Test	Less then 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways

2978 Stitch


2979 Pleat

2980 Hem

2981 Needle


2982 Tailor


2983 Serge


2984 Weft


2985 Woolen

2986 Measure


2987 Selvage


2988 Thread


2989 Placket


2990 Dart

2991 Seam

2992 Flannel


2993 Thimble


2994 Suit